

Technical Data Sheet

Master Gap Wax

Description

Master Gap Wax is a soft wax developed for quickly and easily filling gaps in Sheet Wax, patching, fixturing, and filleting. **Master Gap Wax** is applied at room temperature and can be used as an alternative to clay, especially when adhesion to the composite material is preferred.

Physical Properties

- | | |
|------------------------------------------------|-----------------|
| • Colour: | Green |
| • Ring & Ball Softening Point (°C): | 62.7 (+/- 3.3°) |
| • Flash Point (°C): | 240.5 |
| • Relative Density (g/cc): | 0.9 (/ - .05) |
| • Viscosity: | Paste |

Health and Safety

Please see safety data sheet.

*A product Safety Data Sheet should be obtained from Ellsworth Adhesives Ltd prior to use.
ATTENTION: Before handling, read product information, Product Safety Data Sheets and container labels for safe use, and any physical and/or health hazard information.*

Issue date: 22 April 2021 Ellsworth Adhesives Ltd
Registered Office: 2 Langlands Avenue, Kelvin Business
Park, East Kilbride, Glasgow, G75 0YG, United Kingdom Registered No: 122624
Tel: +44 (0) 1355 231122 Fax: +44 (0) 1355 235266 Website: www.ellsworthadhesives.co.uk

Warranty: The information given in this product data sheet are believed to be fully accurate. However, Ellsworth Adhesives Ltd shall not be liable for its content and make no warranty with respect thereto. For additional information we request you to contact Ellsworth Adhesives Ltd - visit our website: www.ellsworthadhesives.co.uk